

**EPOXY ROD****(GLASS EPOXY MOULDED ROD)**

GRADE: LRG

COLOUR: NATURAL GREEN COLOUR

DIAMETER: 6 - 60MM

DESCRIPTION: COMPOSITE RODS OF GLASS WITH EPOXY. WITH HIGH FLEXURAL & COMPRESSION STRENGTH, DIMENSIONAL STABILITY, LIGHTWEIGHT & EXCELLENT MACHINING. RODS ARE ROLLED & MOULDED.

<u>PROPERTIES</u>	<u>AVERAGE TEST RESULTS</u>	<u>UNIT</u>
BENDING STRENGTH	241	Mpa
COMPRESSION STRENGTH (AXIAL)	241	Mpa
WATER ABSORPTION	0.5 (13mm)	%
DENSITY	1.70 -1.79	g/cm ³
// BREAKDOWN VOLTAGE (IN TRANSFORMER OIL AT 90+-2°C)	15	Kv

THIS DATA, WHILE BELIEVED TO BE ACCURATE AND BASED ON RELIABLE ANALYTICAL METHODS, IS FOR INFORMATIONAL PURPOSES ONLY. DATA SUPPLIED ABOVE ARE "TYPICAL VALUES", NOT TO BE CONSIDERED "SPECIFICATION VALUES"